

PS960

PRODUCT DATA SHEET

Description: *Pressure Sensitive/ Heat Seal film combination
Typically, the film is heat sealed to the backside of
fabrics. Designs cut from this are tacked to clothing
prior to embroidery stitching.*

PO Box 150
10510 Randall Ave.
Aurora, IN 47001
Ph: 800-519-7567

Features & Benefits

- Anti-fray coating
- Repositionable
- Easy to handle
- Light tack for most garments
- Provides stiffening for handling
- Will not gum up embroidery needles

STANDARD PRODUCT CONSTRUCTION

- Combined adhesive thickness: .002"
- Width: 14.0" and 51"
- Carrier: Release polyester film

Product Applications

- Pre-apply to decoratives for embroidery applications
- Multi-layer, multi-color decoratives and appliques

TACK PROPERTIES OF BACKED DECORATIVES TO CLOTHING

- 180 deg. Peel (oz/in)
 - to twill: 3.0
 - to cotton: 8.0
 - to fleece: 8.0

Recommended Application Conditions

Backing of fabrics/designs

- Temperature: 320-340°F
- Dwell: ~3 sec

- Loop Tack: N/A

Application of backed decorative

- Hand press at room temperature

- Static Sheer: N/A

Note: The backed decorative can be heat pressed to garment before or after it is sewn down to increase the bond, but it will not be repositionable after heat pressing.